Pharmacy Plus Bluetooth Enabled Refrigerator

47L Pharmacy Plus Upright Fridge with Solid Door

GDMAcode PPSR47BT-UK

SKU code 444411305







Key features

- ✓ Local monitoring and alarm history via Bluetooth
- ✓ Power failure alarm with backup battery powered recording
- √ Solid and glass door options
- ✓ Intelligent fan management system for enhanced performance











Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



| Gross Capacity (litres) | 47L |
|---|---|
| Net Capacity (litres) | 30L |
| Unit External Width (mm) | 475mm |
| Unit External Depth (mm) | 445mm |
| Unit External Height (mm) | 565mm |
| Product Weight (kg) | 17.5Kg |
| Packed Width (mm) | 490mm |
| Packed Depth (mm) | 530mm |
| Packed Height (mm) | 620mm |
| Packed Weight (kg) | 21.5Kg |
| Country of Origin | UK |
| Internal Dimensions (mm) (WxDxH) | 403mm x 354mm x 425mm |
| Temperature Range | +2°C to +8°C |
| Colour | White/Green |
| External Finish | Painted Steel |
| Internal Finish | HIPS* |
| Type of plastic | SRL800 (HIPS/ABS mix) |
| Door Finish | Painted Steel / Solid |
| Door Type | Solid |
| Door Style | Hinged, Reversible |
| Door Liner | Flat |
| Number of Door Trays | n/a |
| Number of Door Tray Positions | n/a |
| Door Open Depth (mm) | |
| Replacement Door Seal | 905mm No |
| Open Door Sensor | Yes |
| Lock | |
| Adjustable Feet (number & position) | Yes, 2 Keys 2 adjustable (front) |
| Porthole | |
| | Yes |
| Porthole Size | 16mm |
| Porthole Location | Rear LH Corner |
| Temperature Display on Panel | Yes |
| Temperature Alarm | Yes |
| Remote Alarm Contacts | Yes |
| Audible Alarms | Yes |
| Visual Alarms | Yes |
| Number of Shelves/Drawers |] |
| Number of Shelf Positions | 3 |
| Shelf Size (mm) (WxDxH) | 416mm x 200mm x 6mm |
| Shelf Material | Polythene Coated Wire |
| Drawer Size (mm) (WxDxH) | n/a |
| Drawer Material | n/a |
| Number of Baskets |] |
| Basket Material | Polythene Coated Wire |
| Basket Size (mm) (WxDxH) | 396mm x 165mm x 150mm |
| Interior Light | Yes |
| t factor was an an | |
| Light Type | LED |
| Light Type Light Activation | LED Door Switch / Controller |
| | Door Switch / Controller Yes - Axial |
| Light Activation | Door Switch / Controller Yes - Axial No |
| Light Activation Fan | Door Switch / Controller Yes - Axial No Auto (Off Cycle) |
| Light Activation Fan Spark Free Defrost setting Controller Type | Door Switch / Controller Yes - Axial No |
| Light Activation Fan Spark Free Defrost setting | Door Switch / Controller Yes - Axial No Auto (Off Cycle) |
| Light Activation Fan Spark Free Defrost setting Controller Type | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free HCFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free HCFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type Blowing Agent | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HCFC Free HCFC Free HCFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type Blowing Agent Anti Microbial Handle | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HCFC Free HCFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HCFC Free HCFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |
| Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets | Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes |

